720P HD H.264 IR-10M IP Camera

CAM666HIR (PoE)

- 720P CMOS Sensor
- H.264/ MJPEG/ MPEG4 Triple mode & streaming
- Support D-WDR / DNR /8 steps manual shutter
- 30FPS@1280x800
- Onvif Compliant
- IR distance up to 10 meters
- Digital I/O: 1 In / 1 Out
- IP-66 standard
- 3GPP for monitoring via smart phone
- Embedded PoE (CAM666HIR-PoE)
- Free 36CH recording software

Specification

Hardware

CPU	ARM 9
RAM	128MB
Flash	16MB
Image Sensor	1/4" CMOS, Mega pixel
Lens	4.2mm @ F1.6
Illumination	IR On: 0 Lux
IR Distance	10 Meters
Digital I/O	1 In / 1 Out
Water Proof	IP-66 standard
Power Supply	Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adaptor: DC 12V, 1A
Dimensions	W83 x H79.5 x L182.5 mm
Temperature	-10°C ~ +45°C

Network

Ethernet	10/ 100 Base-T
Network Protocol	HTTP, HTTPS,TCP/IP, RTP/RTSP, UDP, 3GPP, NTP, SMTP, FTP, PPPoE, Samba, DHCP, DDNS, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE802.1x, IPv4/IPv6

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7,IE8, FireFox, Safari, Chrome,Opera
Suggested	Intel Dual Core 2.53GHz, RAM: 1G, Graphic card: 128MB onboard RAM

System

Video Resolution	1280x800, 1280x720, 640x480, 320x240, 176x144
Compression Format	H.264/ MJPEG/ MPEG-4
Frame Rate	Up to 30 FPS@1280x800
Video Bitrate Adjust	CBR, VBR
Triple Streaming	Yes
3GPP	Yes, Live view with smart phone
Image Snapshot	Yes
Video Adjust	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Manual Shutter adjust, D-WDR, Night Mode, Flip, Mirror, Digital Noise reduction, Exposure, Day & Night
Motion Detection	Yes, 3 different areas
Privacy Mask	Yes, 3 different areas
Pre/ Post Alarm	Yes, configurable
Security	Password protection IP address filtering, HTTPS encrypted data transmission, IEEE802.1x port-based authertication, QoS/DSCP
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely

Event System

Event Trigger	Motion Detection, Digital In
Trigger Actions	Send Email, Send to FTP, Save to Samba HDD, Digital out

Package List

PoE Model doesn't include power adaptor